13 May 2011

Product description

Anatolia above-ground access point ensures easy and cost-effective installation and service.
High quality materials and components for long life time. Supplied ready-to-install with splice cassettes for reducing installation time and network roll-out.
Splice box and backboard can be taken out of the cabinet for better access during services.
IP Termination splicebox with lid for optimal and cost-effective protection of splices.
Pre-installed with metal backboard, splice cassettes, connection set and fiber tube management system.
Ready-to-install system solution for FTTH network.

Product features

- Easy access

- Proven Technology

- Splice box and backboard can be taken out of the cabinet for better access during installtion and services

- Tube management divider inside the splice box

- Anti graffiti and anti sticker protection available

- Cabinet key lockable

Anatolia Telecom &Advanced Material Technlogies R&D LTD .Istanbul Turkey .sales@anatoliacom.com Tel:0090 5321541859

Technical characteristics

Cabinet:

Material:	1.5 mm galvanized steel. Zink coated on all surfaces.
Paint:	Grey RAL 7037 polyester powder coating.
Lock:	Hole in front door for Anker lock (lock not included - locking cam for Anker lock included). Teardrop protection against dust and vandalism. Ruko cylinder lock available as option.
IP degree:	IP34 Hidden slots for natural ventilation reducing moisture level.
Root:	Integrated adjustable root.
Fixing bars:	Fixing bar for securing cables and tubes integrated in root and below backboard.
Backboard:	Metal backboard with bracket for cable / tube over length, and fixing points on the sides for fixing over length cable / tube with strips.
Dimension:	675x462x198mm (HxWxD) above the ground, 760x462x198mm under he ground

Termination Box:

Material:	ABS	
Base colour:	Grey, RAL 7035	
Ingress protection:	IP66/67 EN 60529	
Impact resistance:	IK 07 EN 50102	
Halogen free:	DIN /VDE 0472	
Flammability rating:	UL 94 HB	
Backboard:	1.5 mm galvanized steel. Zink coated on all surfaces.	
Tube divider:	Steel, polyester powder coating, Grey RAL 7037	
Splice tray:	ABS, 8x 12splices each for ANT splices protector	
Temperature:	short term	-40…80°C
	Continuous	-40…60°C

13 May 2011

Ordering

Product description: Product code:

FttH Streetcabinet for 48connections   **NL_DS_70010**

Packing and labeling

All products suitably packed in recyclable materials and clearly labeled with Anatolia article number and description.